



## Wall box advices











Our product fit on 67/68mm diameter wall box by screwing.  
 Distance of 60mm between two screws.  
 More precisely Elo range is adapted to single gang round wall box having a dimension of 80mm max.

You can:

- either directly order us the box for hollow walls OBO BETTERMANN that are perfectly suited to our equipment.  
 Ø68mm 45mm deep







- either use wall box in the list below. We advice suppliers as Alombard, Sarel and Capri because their boxes leave more possibilities for position installation choice.

	Dry wall	Multi material	Masonry
<b>Sarel</b>	Murabox 2 ref.12802/12852  Murabox E ref.13802/13852 		
<b>Alombard</b>	Alfix ref. ALB71340/ALB71341 	Multifix Plus ref. ALB71320/ALB71322  Multifix Air ref. ITM35001/ITM35002 	Modulo ref. ALB71361 
<b>Capri</b>	Capriclips ref. 736819/736859 		Capribox ref. 710899/710999 



Realitem

<b>Hager</b>	ref. WE741		ref. WE840
<b>Simon</b>	serie 27 ref. 32713 -35		
<b>Debflex</b>	ref. 718357		
<b>Legrand</b>	Batibox* ref. 80041/80051  89 mm Batibox Energy* ref. 80021/80031  89 mm	Batibox* ref. 80101/80121  87 mm	Batibox ref. 80108 

\* You can use these references but you need to cut excess material sticking of our mechanism.

## Installation advice

Our products require before mounting a support with a good flatness.

### Dry Wall :

To ensure this flatness, the mechanism must rest against the flange of flush wall box in the case of drywall painted or wallpapered.

In the case of a decorative coating structured (high relief), first lightly sand the contact surface and the overlap surface in order to ensure the optimum clip.

### Masonry :

During installation of flush wall box, consider the plaster layer thickness which stay to apply. The wall box mustn't to exceed from the wall coated. It must be flush with the coating.

In the case of a decorative coating structured (high relief), first lightly sand the contact surface and the overlap surface in order to ensure the optimum clip.

